

DATA PROJECTORS

D535



The Vivitek D535 digital projector is distinctive in design, lightweight and packed with user-friendly features.

Connectivity options for the D535 including HDMI v1.3 and is DLP 3D-ready, making it ready for the latest multimedia applications. With a high brightness level of 3200 ANSI Lumens and a weight of only 1.9kg, the Vivitek D535 is a very portable solution to deliver sharp, vibrant pictures and presentations.

Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- Native XGA Resolution and able to display up to UXGA (1600 x 1200)
- Keypad lock feature to avoid accidental change to the setting
- DLP link 3D-ready
- Rapid on/off feature
- Enhanced color and display adjustments
- 3200 ANSI Lumens of brightness with a 3000:1 contrast















Specifications	
Brightness	3200 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Max. Resolution	UXGA (1600 x 1200) @60Hz
Contrast Ratio	3000:1 (Full On/Off)
Lamp Life and Type	≈3000/4000 Hours (Standard/Economy Mode), 240W
Lamp Part #	5811116310-SU
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	1.92 to 2.14:1 (Distance/Width)
Image Size (Diagonal)	40" to 300" (1.0 to 7.6 m)
Projection Distance	1.0 to 10.0 m
Projection Lens	F = 2.52-2.73, f = 24.34-25.95 mm
Zoom Ratio	1.1:1 Manual Zoom/Focus
Aspect Ratio	4:3 Native, 16:9, 16:10 Compatible
Offset	128%
Keystone Correction	±15° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	2 Watt
Remote Control	Card Type IR Remote
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3, VGA-In, Composite Video, S-Video, Mini-Jack Audio-In, RCA Stereo Audio, RS-232c
Security	Kensington® Lock Port
Weight	1.9 Kg
Dimensions (W x H x D)	261 x 78 x 190 mm
Noise Level	35dB/29dB (Normal / Eco Mode)
Power	Supply: AC 100-240V Consumption: 230W (Economy Mode), 300W (Standard Mode), <1W (Standby Mode)
Warranty Education Warranty	3-Year Warranty, 1-Year or 1,000h on Lamp 5-Year Warranty, 3-Year (or max. Lamp Lifetime)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Lens Cap, Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	8 14964 33467 1