



**The All-Round Multi-Media Projector**

The Vivitek D859 digital projector combines the best features, performance and value for money. The Vivitek D859 includes multiple connectivity options, including DVI-I and HDMI, and thanks to its DLP® technology and BrilliantColor™ it can display outstanding picture quality and saturated colors.

**Features**

- Native XGA resolution and able to display up to UXGA (1600 x 1200)
- 3600 ANSI Lumens of brightness and a 3000:1 contrast ratio
- 3D-Ready via DLP® Link™
- Sealed optical engine
- Top-loading for lamp easy replacement
- VGA–output for display on a secondary monitor
- Keypad lock prevents accidental system adjustments
- Enhanced color and display adjustments
- Network-ready for integration and system administration via RJ45

Specifications	
Brightness	3600 ANSI Lumen
Native Resolution	XGA (1024 x 768)
Max. Resolution	UXGA (1600 x 1200) @60Hz
Contrast Ratio	3000:1 (Full On/Off)
Lamp Life and Type	4000/2500 Hours (Standard/Boost Mode), 230W
Lamp Part #	5811116781-SU
Throw Ratio	1.60-1.92 (Distance/Width)
Image Size (Diagonal)	30" to 300"
Projection Distance	1 to 10m
Projection Lens	F = 2.52 - 2.73
Zoom Ratio	1.2x
Aspect Ratio	4:3 Native, 16:10 & 16:9 Compatible
Offset	128%
Keystone Correction	Auto Keystone, ±15° Vertical
Color Spectrum	16.7 Million
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	10 Watt
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3, VGA-In, VGA-Out, Composite Video, Mini-Jack Audio-In, Mini-Jack Audio-Out, RCA Stereo-In, RJ45, RS-232c, USB (Service), Microphone (Mini-Jack)
Security	Kensington® Lock Port
Weight	2.7 kg
Dimensions (W x H x D)	306 x 104 x 206 mm
Noise Level	36dB/33dB (Normal/Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 240W (Standard Mode), 290W (Boost Mode), <1W (Standby Mode)
Warranty	3-Year Warranty, 1-Year or 1,000h on Lamp
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Lens Cap, Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	814964335364

