

BUSINESS PROJECTORS





The All-Round Multi-Media Projector

The Vivitek D853W digital projector combines the best features, performance and value for money. The Vivitek D853W includes multiple connectivity options, including DVI-I and HDMI, and thanks to its DLP® technology and BrilliantColor™ D853W can display outstanding picture quality and saturated colors. Also thanks to its long-life lamp with up to 6000 hours operations, the projector is low in maintenance cost.

Features

- Native WXGA resolution and able to display up to UXGA (1600 x 1200)
- 3200 ANSI Lumen of brightness and a 3000:1 contrast ratio
- 3D-Ready via DLP[®] Link[™]
- High-efficiency lamps that last up to 6000 hours (in economy mode)
- VGA-output for display on a secondary monitor
- Keypad lock prevents accidental system adjustments
- Enhanced color and display adjustments
- Network-ready for integration and system administration via RJ45



Specifications	
Brightness	3200 ANSI Lumen
Native Resolution	WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200) @60Hz
Contrast Ratio	3000:1 (Full On/Off)
Lamp Life and Type	6000/4000 Hours (Standard/Boost Mode), 220W
Lamp Part #	5811116713-S
Throw Ratio	1.52-1.76 (Distance/Width)
Image Size (Diagonal)	40" - 300"
Projection Distance	1.5 - 10 m
Projection Lens	F = 2.55 - 2.72, f = 21.35 - 24.49 mm
Zoom Ratio	1.15x
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	123%
Keystone Correction	Auto Keystone ,±15° Vertical
Color Spectrum	16.7 Million
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	10 Watt
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3, DVI-I, VGA-In, VGA-Out, Composite Video, Mini- Jack Audio-In 2x, Mini-Jack Audio-Out, RCA Stereo-In, RJ45, RS-232c, USB (Service), Microphone (Mini-Jack)
Security	Kensington [®] Lock Port
Weight	2.7 kg
Dimensions (W x H x D)	306 x 104 x 206 mm
Noise Level	36dB/33dB (Normal / Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Standard Mode), 280W (Boost Mode), <1W (Standby Mode)
Warranty Education Warranty	3-Year Warranty, 1-Year or 1,000h on Lamp 5-Year Warranty, 3-Year (or max. Lamp Lifetime)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Lens Cap, Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	814964335173

© Copyright 2013 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Address: Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands, Tel: +31 20 655 0960, Fax: +31 20 655 0999, E-Mail: info@vivitek.eu