

EDUCATION PROJECTOR

D873ST



The D873ST is designed to cater for the education needs. The D873ST projects an 82" image diagonal from less than 1 meter distance 0.6:1 T.R. With a brightness of 3000 ANSI Lumens and outstanding contrast ratio of 15.000:1 it delivers a perfect image display. The projector is designed for use in any classroom or is perfect solution wither for small office room and home office. With its light weight and compact form factor this is a short throw projector for easy installation.

Features

- Native XGA resolution and able to display up to UXGA (1600 x 1200)
- Sharp and detailed image quality with DLP® and BrilliantColor™ technologies
- Large 82" screen size from only 1 meter away
- 3600 ANSI lumens of brightness with a 15000:1 contrast
- High-efficiency lamp that lasts up to 4,000 hours (in Standard Mode)
- 3D-Ready via DLP® Link™
- Enhanced color and display adjustments
- Convenient top loading design to easily replace lamp
- Sealed optical engine to keep dust out
- Network-ready for integration and system administration via RJ45
- 10W audio speaker

Product Pictures











| Specifications | |
|---|---|
| Display Type | DLP |
| Brightness | 3600 ANSI Lumens |
| Native Resolution | XGA (1024 x 768) |
| Maximum Resolution | UXGA (1600 x 1200) |
| Contrast Ratio | 15000:1 |
| Lamp Life and Type | 3,000 /4,000 Hours (Std./Eco Mode), 240W |
| Throw Ratio | 0.6:1 (82" @ 1m) |
| Image Size (Diagonal) | 41" - 328" |
| Projection Distance | 0.5 - 4m (1.6ft to 13.2ft) |
| Projection Lens | F=2.7, f = 6.82mm |
| Zoom Ratio | Fixed Lens |
| Aspect Ratio | 4:3 Native, 16:9 Compatible |
| Offset | 128% ± 10% |
| Keystone Correction | Vertical ± 40% (±40 Step) |
| Horizontal Frequency | 15, 30-90 KHz |
| Vertical Scan Rate | 43 - 85 Hz |
| Speakers | 10W (Mono) |
| Lens Shift Range | N/A |
| Video Compatibility | SDTV(480i), EDTV (480p), HDTV (720p, 1080i), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM |
| I/O Connection Ports | HDMI v1.3 (x2), VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini- Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service) |
| Projection Method | Table Top, Ceiling Mount (Front or Rear) |
| Security Solutions | Kensington® Security Slot, Security Bar, |
| | Keypad Lock |
| Dimensions (W x D x H) | 285 x 261 x 121.8 mm |
| Weight | 2.7Kg |
| Noise Level | 35dB/32dB (Normal/Eco Mode) |
| Power Supply | AC 100-240V, 50/ 60Hz |
| Power Consumption | 250W (Eco Mode), 300W (Normal Mode), <0.5W (Standby Mode) |
| Warranty | 3 Years, 1 Year (or 1,000h) on the Lamp 5-Year Warranty, 3-Year (or 2,000 hours) |
| Education Warranty Standard Accessories | |
| Stanuaru Accessories | AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit |
| Optional Accessories | Replacement Lamp, Remote, Carrying Case |
| UPC | 814964 335906 |
| | |









